pera ion an al



an fac rer aygene ompany imi ed

eaning

б.			
7.			
8.			
9.			
10.			
11.			
12.			
13.			
14.			
15.			
16.			

4.

5.

	<52

echnical pecifica ions

rod c escrip ion ech

rod c escrip ion echnical pecifica ions



				_
GF	NF	SP	FF	`D®

8 4		2163



o or o pling and isassembling

oor elease	P
•	
•	RCF IN THE
\checkmark	
to open the door when power is gone off, please refer to	75Emergency Door Release'.

ns alla ion

ower

c ion

c ion

ower and oor elease



• Only use appropriate centrifugal tubes and do not exceed the speed beyond the tube' s max



For safety, the 'Imbalance Cutoff' function is

GENESPEED®

- e ing he al e

pera ion

ey

e ing peed □ RPM/RCF

e ing ime

□ SOFT START /STOP

e ing he

nc ions

🗆 TIME

e ing

T

c ion

▶

 \Box PROG □ START/STOP

nc ions of on rol anel

J

ng Speed

al e

- e ing he al e

RPM

RPM

RCF

O MIN/Cell

Setting Time Conducting Function

0

SOFT

TIME

0

STOP

START

STOP

DOOR

PROG

Setti

[▲▼] buttons pressed over 5





GENESPEED®

rogram ave

c ion

rogram ave ecall

c ion

- While running, the START LED' is turned on.

c ion

- **A V**
- .
- e ing he al e

- e ing he al e
- ► c ion

 $\blacktriangle \blacksquare$

e ing he ime al e













eplacemen of se





mergency oor elease

- :
- ▲▼
- •
- rogram ecall

1.

2.

3.

4.

- •
- •
- •
- •







c ion



ain enance

er par of ins r men





